

specgroup

Page: 1

November 4, 2014

#### Abstract

A procedure to group spectral channels

## 1 Instruments/Modes

Instrument	Mode
EPIC,RGS	IMAGING, TIMING

### 2 Use

pipeline processing	yes	
interactive analysis	yes	

# 3 Description

**specgroup** is a tool which allows a flexible, user-defined grouping of channels in a spectrum. It extends the functionality of the ftool GRPPHA to allow the user more options of grouping the spectrum based on statistical criteria.

Channels can be predefined as BAD (i.e. not to be used) either by using definitions from a calibration file or by specifying the channels or energy range to exclude on the command line.

The treatment of the special cases of the first and last group is user definable (section 4.4).

### 3.1 Setting bad channels

The quality of spectral channels may be set to bad by choosing the appropriate option. If set bad, channels will not be considered when grouping channels with one of the statistical methods. However, if a range or regular binning is specified which includes these bins then this will take precedence and the quality of these channels will be set to good.

The options are:

Page: 2

specgroup spectrumset=srcspec.ds setbad=CCF

in which case the channels to exclude from spectral fitting will be read from a calibration file.

specgroup spectrumset=srcspec.ds setbad='0:10,790:799'

in which case the channels from 0 to 10 and 790 to 799 will be set bad.

specgroup spectrumset=srcspec.ds setbad='0:0.2,10.0-15.0' units=KEV

in which case the channels with energy between 0 and 0.2 keV or 10 and 15 keV will be set to bad.

 $specgroup\ spectrumset = srcspec.ds\ setbad = no$ 

in which case no channels will be excluded before the spectrum is grouped.

### 4 Grouping options and examples

### 4.1 User defined ranges

The spectrum may be grouped using a fixed set of ranges in channel space, e.g.:

specgroup spectrumset=srcspec.ds groupedset=SpecGrp.ds ranges="1:10,11:50"

which will produce two groups: the first from spectral channel 1 to spectral channel 10 and the second from spectral channel 11 to 50. The rest of the spectrum will remain ungrouped. Note that the spectral channel refers to the channel number contained in the *CHANNEL* array in the spectrum. This is not necessarily the same as the bin number of the spectrum.

The ranges can also be defined in photon energy units (KEV), e.g.:

 $specgroup\ spectrumset = srcspec.\ ds\ grouped set = SpecGrp.\ ds\ ranges = "0.0:0.4,1.0:2.0"\ units = \textit{KEV}\ rmfset = m1.rmf$ 

which will produce a group containing spectral bins with *central* energies between 0.0 and 0.4 keV and another with central energies between 1.0 and 2.0 keV. The conversion between spectral channel and photon energy is given in the *EBOUNDS* extension of an OGIP compliant response file (see George et al....). Therefore if ranges are given in keV a redistribution matrix (RMF) must be supplied otherwise the error, *NoRMFsupplied* will be issued.

This option may be used in conjunction with the regular binning option and/or one of the statistical options. In which case the range grouping is applied first and the subequent options are applied to the remaining ungrouped bins.

### 4.2 withRegularBins

This is a simplistic option which allows a spectrum, or part of a spectrum, to be grouped in regular intervals, e.g.

Page: 3

specgroup spectrumset=srcspec.ds groupedset=SpecGrp.ds regbinstart=1 regbinend=300 regbinwid=10

which would make 30 groups of 10 bins each from the initial 300 bins in the spectrum. Note that in this case the bins refer to the position in the spectrum and start from bin 1.

This option may be used in conjunction with one of the statistical options. In which case the regular bin grouping is applied first and the statistical grouping is applied to the remaining ungrouped bins.

### 4.3 Statistical grouping

One of the following statistical tests may be applied to the data to calculate spectral groups.

- 1. Minimum number of counts
- 2. Minimum signal-to-noise ratio
- 3. Minimum ratio above the background

Only one of these may be selected otherwise the error MoreThanOneStatMethod will be issued.

The chosen statistic will be applied to the spectrum starting from the lowest to the highest bin (normally lowest to highest energy) by default. This may be reversed by setting the option hightolow=yes.

The treatment of the last group is user selectable (see section refspecgroup:options:lastbin).

### 4.3.1 Minimum number of counts

With this option the spectrum is grouped such that each group contains a minimum number of (source+background) counts. This is the equivalent to the "group min 25" command available in the ftool GRPPHA. e.g.

specgroup spectrumset=srcspec.ds mincounts=50

which would produce a group for each set of bins which contained 50 or more counts. By default the grouping begins from the low energy end (usually the first channel). To reverse this and start from the high energy end use:

 $specgroup\ spectrumset = srcspec.ds\ mincounts = 50\ hightolow = yes$ 

Note this grouping is based on the number of counts in the source spectrum, which may also contain background.

### 4.3.2 Minimum signal-to-noise ratio

This sets spectral groups such that each group contains a minimum signal-to-noise ratio (S/N). The calculation of the ratio will take the area-normalised background into account if a background spectrum is provided. e.g.:

 $specgroup\ spectrumset = srcspec.\ ds\ minSN = 6.0\ backgndset = bgdspec.\ ds$ 

Page: 4

would make groups with a minimum S/N of 6 where S/N is given by:

$$S/N = (source - background * areanorm)/sqrt(source + background * areanorm^2)$$
 (1)

#### 4.3.3 Minimum ratio above background

Defines groups where each one contains a minimum ratio of the source signal to the background counts:

$$ratio = (source - background * areanorm)/(background * areanorm)$$
 (2)

### 4.3.4 Copy from a template spectrum

The grouping can be copied directly from another spectrum by:

 $specgroup\ spectrumset=bgndspec.ds\ grouptemplate=sourcespec.ds$ 

This would group the background spectrum in exactly the same way as the source spectrum.

### 4.4 Treatment of the last bin and other ungrouped bins

In the case where the last few bins of the spectrum do not meet the required statistical criterion for a normal group it may be treated in several ways:

- 1. Leave the bins ungrouped and set their quality to bad:
  - lastbin="setbad"
- $2. \ \,$  Group them and set their quality good:
  - lastbin="owngroup"
- 3. Add these bins into the final group:
  - lastbin="addtogroup"

The default is to add these bins onto the adjacent group. A different option may be selected by e.g.

specgroup spectrumset=srcspec.ds mincounts=25 lastbin="setbad"

In principle, a set of user-defined ranges could leave ungrouped bins in the middle of the spectrum. These will also be treated according to the *lastbin* parameter setting.

### 4.5 Other grouping options

### 4.5.1 Minimum resolution

If the number of counts in a spectrum is very high then a statistical grouping can dramatically oversample the instrument resolution. This can cause problems during spectral fitting because the bins are then not completely independent.

A minimum energy width of each group can be enforced by setting the parameter oversample. e.g.

specgroup spectrumset=srcspec.ds mincounts=25 oversample=3 rmfset=myrmf.ds

would ensure that no group was narrower than 1/3 of the full width half maximum (FWHM) resolution at the central photon energy of the group.

 $\Delta E >= FWHM(E)$ 

where the values of FWHM(E) are read for a given instrument from a calibration file (XMM\_SPECQUAL\_nnnn.CCF for XMM instruments).

### 4.6 Associated file keywords

The task will write the associated background, response and effective area filenames into keywords in the output spectrum header so that they can be picked up by spectral fitting software.

specgroup spectrumset=srcspec.ds addfilenames=yes arfset=myarf.ds
rmfset=myrmf.ds backqndset=mybqnd.ds

will fill the ANCRFILE, BACKFILE and RESPFILE keywords in the spectrum header. If the background, ARF or response files are not given on the command line then these keywords will be set to 'NONE'.

Some spectra contain the header keyword 'GROUPING=0'. If this exists in the header of the input spectrum it will be removed from the output file. All other keywords will be copied over.

### 5 Default behaviour

The command:

specgroup spectrumset=srcspec.ds

will have the following behaviour:

- Channels defined as bad for that instrument in the corresponding XMM\_SPECQUAL CCF will be set BAD.
- All keywords, ANCRFILE, BACKFILE, RESPFILE, will be set to "NONE"
- The data will be grouped such that each input channel is in a group of its own

To set the channels bad and leave the data ungrouped use the command:

specgroup spectrumset=srcspec.ds mincounts=0

# 6 Spectra made from combined instruments

It is possible to produce a spectrum from combined instruments using the tasks **rgscombine** or **epicspeccombine**. The combined spectra have an undetermined contribution from each instrument and so assumptions have to be made when grouping the spectra. For simplicity, **specgroup** uses the settings of *MOS1* if the spectrum has been made from a combination of EPIC cameras and the settings of *RGS2* if made from a combination of RGS1 and RGS2.

Page:

7 Parameters				
This section documents the				
Parameter	Mand	Type	Default	Constraints
spectrumset	yes	dataset		
The name of the input spec	trum in cou	nts v channe	el space.	
overwrite	no	boolean	no	
Whether to overwrite the in	nput spectru	m with grou	ping information or t	to produce a new file (default)
groupedset	no	dataset	SpecGrp.ds	
The name of the grouped of	utput spectr		1 1	
backgndset	no	dataset		
The name of the backgroun	d spectrum			
mincounts	no	int		
The minimum number of co	ounts (source	e+backgroun	d) to use when group	ping
minSN	no	real		
The minimum signal to nois	se ratio to u	se when grou	ıping	
ratioabovebgnd	no	real		
The minimum ratio of source	ce to backgr	ound to use	when grouping	
grouptemplate	no	dataset		
The name of a spectrum from	om which to	copy the gro	ouping parameters	
oversample	no	real		
			if oversample=3 ther	the minimum width of a group
is $1/3$ of the resolution FW.	HM at that	energy.		
ranges	no	string		
				ned in channels, or as decimals if
				ngly. The beginning and end of
a range may be seperated b e.g. "2-20,63-97" or "0.2-0.5			h. Multiple ranges sh	hould be seperated by a comma.
units	no	choice	CHAN	CHAN KEV
The units used for ranges -				
	0 021001			

regbinstart

no

int

Page: 7

First channel to use if grouping done by regular bins

~	regbinend	no	int		
---	-----------	----	-----	--	--

Last channel to use if grouping done by regular bins

regbinwid	no	-int	

Number of channels to combine in each group if grouping done by regular bins

rmfset no dataset
-------------------

The name of a redistribution matrix used to define the energy of the spectral channels.

hightolow	no	boolean	false	

Whether to group from low to high (false) or high to low (true) energies.

addfilenames	no	boolean	true		

Whether to set the ANCRFILE, RESPFILE, BACKFILE keywords in the spectrum header.

arfset	no	dataset	

The name of an effective area (ARF) file. This is purely used as a string to write into the ANCRFILE keyword. The file is not opened.

lastbin	no	choice	addtogroup	addtogroup	setbad
				owngroup	

What to do about ungrouped channels, typically the channels at the end of the spectrum which don't meet the statistical criterion.

$\mathbf{setbad}$	no	string	CCF	CCF	no
				ranges_of_values	.

Whether to set some channels BAD and exclude them from grouping. Options are: "CCF" - to read the BAD channels from a calibration file, "no" - meaning 'take no action' or a range such as "0-10,750-799" may be entered to explicitly specify which channels to set BAD. The range may be defined in channels or keV, consistent with the setting of the units parameter.

### 8 Errors

This section documents warnings and errors generated by this task (if any). Note that warnings and errors can also be generated in the SAS infrastructure libraries, in which case they would not be documented here. Refer to the index of all errors and warnings available in the HTML version of the SAS documentation.

### NoRMFsupplied (error)

The input units for ranges have been set to keV but a redistribution matrix hasn't been supplied.

### MoreThanOneStatMethod (error)

Only one statistical method, e.g. minimum counts, minimum S/N or ratio above background, can be specified

#### InvalidRangeString (error)

The ranges must be entered as '1-10' or '1:10' if specified in channels or as '2.0:4.53' or '2.0-4.53' if specified in keV.

### Page:

### EnergyOutOfRange (error)

The specified energy range is outside the range of energies contained in the spectrum

### RegBinRange (error)

The start bin for regular binning must be  $\xi = 0$ .

### IncompatibleTemplate (error)

The template spectrum has a different number of channels from spectrum to be grouped.

### AmbiguousGrouping (error)

There has been a clash between the ranges and regular binning requested.

### AlreadyGrouped (warning)

A bin which has been requested to be set bad by the **setbad** option has already been grouped and so will stay as a good channel.

corrective action: leave channel as good

### NoMergeGroup (warning)

After grouping has completed and ungrouped channels are treated according to the lastbin parameter selection. Sometimes it is impossible to find a contiguous group to add a given channel to. Contiguous channels which fall in this category are used to form a new group. corrective action: create a new group

## 9 Input Files

- an EPIC spectrum consisting of counts vs P.I. channel.
- a redistribution matrix (RMF) corresponding to the source in question
- an optional EPIC background spectrum consisting of counts vs P.I. channel.

# 10 Output Files

• A spectrum with grouping applied. The grouping is specified in the column GROUPING where a number 1 indicates the first channel in a group and -1 indicates a member of the current group. The quality of each channel is given in the QUALITY column; where 0 = good quality, 1 is bad quality and 2 means dubious.

## 11 Algorithm

Set the grouping ranges using the following order

- 1. User defined ranges
- 2. Regular user defined bins
- 3. Set bad, anything defined as bad



Page: 9

- a) Minimum no of counts
- b) Min S/N
- c) Min ratio above background

Convolve these with the options

- i) Minimum bin width as fraction of energy resolution
- ii) Start from low or high energy end
- iii) Treatment of last bin

Sort groups

## 12 Comments

## References