

Examples of *multiaudience* package use

Boris Veytsman

Date: 2015/07/11 22:49:40

Contents

1	Introduction	3
2	The <code>\CurrentAudience</code> command	3
3	The <code>\showto</code> command	3
4	The <code>showto</code> environment	3
5	Use of verbatim text	4
6	Syntactic sugar	4
6.1	Admins-only subsection	5

1 Introduction

We defined three audiences:

```
\SetNewAudience{admins}  
\SetNewAudience{devs}  
\SetNewAudience{execs}
```

2 The `\CurrentAudience` command

The current audience is `\CurrentAudience`.

The current audience is admins.

3 The `\showto` command

Note the nesting here:

```
\showto{admins}{This text is visible to admins only\footnote{And  
admins see a footnote}.}  
\showto{admins, devs}{This text is visible to admins and  
devs. \showto{devs}{This text is visible to devs.}}  
\showto{-, admins}{This text is \emph{not} visible to admins.}  
This text is visible to everybody\footnote{And everybody sees a  
footnote}.
```

This text is visible to admins only¹. This text is visible to admins and devs.
This text is visible to everybody².

4 The `shownto` environment

```
\begin{shownto}{admins}  
This is for admins only.  
\end{shownto}
```

This is for admins only.

```
\begin{shownto}{-, admins}  
This is for everybody \emph{but} admins.  
\end{shownto}
```

¹And admins see a footnote

²And everybody sees a footnote

5 Use of verbatim text

```
\begin{shownto}{-,execs}
We cannot use \texttt{verbatim} inside shownto, but we can use
\texttt{input} with \texttt{verbatim} inside.
```

```
We also can use \texttt{path} and \texttt{url} from hyperref package:
\path{a$2}, \url{http://borisv.lk.net/cv/cv.html\#Publications}.
\input{verbatim}
```

```
We also can use \texttt{path} and \texttt{url} from hyperref package:
\path{a$2}, \url{http://borisv.lk.net/cv/cv.html\#Publications}.
\end{shownto}
```

We cannot use `verbatim` inside `shownto`, but we can use `input` with `verbatim` inside.

We also can use `path` and `url` from `hyperref` package: `a$2`, <http://borisv.lk.net/cv/cv.html#Publications>.

This is a piece of verbatim text.
Special symbols: `~!@#%&*{<>{}`"

Another option is the use of `\SaveVerb` and friends from `fancyvrb` package:

```
\begin{SaveVerbatim}{SavedVerb}
This is a verbatim line: ~!@#%&*{:"'<>?
\end{SaveVerbatim}
```

```
\begin{shownto}{-,devs}
  \UseVerbatim{SavedVerb}
\end{shownto}
```

This is a verbatim line: `~!@#%&*{:"'<>?`

6 Syntactic sugar

We have a special footnote command `\Footnote{admins}`{This footnote is for admins only.}.

We have a special footnote command³.

```
\begin{Subsection}{admins}[Admins-only subsection]{This subsection is
  visible only to admins}
We have special sectioning commands.
\end{Subsection}
```

³This footnote is for admins only.

6.1 This subsection is visible only to admins

We have special sectioning commands.

```
\begin{Subsection}{-,admins}[Not for admins]{This subsection is not  
    visible to admins}  
    Another example. \showto{devs}{This is visible to devs only.}  
\end{Subsection}
```